

arcoPlus®

CONNECTOR MODULAR SYSTEMS

large areas roofing , translucent windows and glazing applications

TECHNICAL FEATURES

	THICKNESS STRUCTURE		WIDTH mm	U VALUE W/m²K
	mm	walls		
arcoPlus684	8	4	600	3,3
arcoPlus6104	10	4	600	3,0
arcoPlus6124	12	4	600	2,7
arcoPlus626	20	6	600	1,7
Fire reaction EN 13501	EuroClass B-s1,d0			

DESCRIPTION

Modular systems provided with a specific connector, depending on the type of application. It is particularly suitable in roofing of large areas, translucent façades and glazing applications.

ADVANTAGES

- ❖ Easy and low-cost installation
- ❖ Self-extinguishing
- ❖ Light transmission
- ❖ Resistance to U.V. rays and to hail
- ❖ Thermal insulation




FLAT SELF-SUPPORTING SYSTEMS





arcoPlus®684-6104-6124

th.8-10-12mm - Minimum bend radius R.2,0m




arcoPlus®626


th.20mm - Minimum bend radius R.4,0m




Reinforced AL profile




Square 32mm tube



Square 62mm tube



Covergasket in PC



Connector AL profile

REVERSÒ SYSTEMS (U.V. protection on both sides)



arcoPlus®684-6104-6124 Reversò

th.8-10-12mm



arcoPlus®626 Reversò

th. 20mm

